

---

## Safety Data Sheet

---

# OR90WPM, Part A

---

### Section 1 – Identification

---

Oak Ridge Foam & Coating Systems, Inc  
575 Commercial Ave  
Green Lake, WI 54941  
920-294-6800

Emergency Telephone: (800) 424-9300 Chemtrec  
800-625-9577 (Oak Ridge Foam & Coating Systems, Inc)  
BOTH NUMBERS ARE AVAILABLE DAYS, NIGHTS, WEEKENDS, & HOLIDAYS

**GHS product identifier:** OR90WPM, Part A  
**Other means of identification:** Not available.  
**Product type:** Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Product use:** Component of a Polyurethane System

**Supplier's details:** Oak Ridge Foam & Coating Systems, Inc  
575 Commercial Avenue  
Green Lake, WI 54941

**Email address of person responsible for this SDS:** info@oakridgepoly.com

**Emergency telephone number (24h/7 day):** Chemtrec: (800) 424-9300 or (703) 527-3887

---

### Section 2 – Hazards Identification

---

**OSHA/HCS status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture:**

Acute Toxicity:Inhalation	4
Skin corrosion/irritation	2
Serious eye damage/eye irritation	2B
Respiratory Sensitization	1
Skin Sensitization	1
Specific Target Organ Toxicity (Single Exposure) [Respiratory Tract irritation]	3

#### GHS Label Elements

**Hazard pictograms:**



**Signal word:** Danger

**Hazard Statements:** Harmful if inhaled  
Causes skin and eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

**Precautionary Statements:** Wear protective gloves. Wear eye or face protection. In case of inadequate ventilation, wear respiratory protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification:** Not available.

### Section 3 – Hazards Identification

---

#### Hazardous Components

Weight Percent	Components	CAS-No.
60-100%	Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	9048-57-1
30-60%	Diphenylmethane 4,4'-diisocyanate	101-68-8
3-7%	Homopolymer of methylenediphenyl diisocyanate	25686-28-6
3-7%	Propylene carbonate	108-32-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation. Occupational exposure limits, if available, are listed in section 8.

### Section 4 – First Aid Measures

---

#### Description of first aid measures

**Eye contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get Medical attention immediately.

**Inhalation:** Move exposed person to fresh air. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is laboured, oxygen should be administered by qualified personnel.

**Skin contact:** After contact with skin, wash immediately with plenty of warm soapy water: Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-TamTm, PEG-400) or corn oil may be more effective than soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

### **Most important symptoms/effects, acute and delayed**

#### **Potential acute health effects**

**Eye contact:** Causes eye irritation

**Inhalation:** Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.

**Skin contact:** Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

**Ingestion:** Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

#### **Over-exposure signs/symptoms**

**Eye contact:** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation:** Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma

**Skin contact:** Adverse symptoms may include the following:  
irritation  
redness

**Ingestion:** No specific data

### **Indication of immediate medical attention and special treatment needed, if necessary**

#### **Notes to Physician**

Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

#### **Protection of first-aiders**

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## Section 5 – Fire Fighting Measures

---

**Flash Point:** Closed cup: >110°C (>230°F) [Setaflash]

### Extinguishing media

**Suitable extinguishing media:** Foam, CO<sub>2</sub> or dry powder

**Unsuitable extinguishing media:** Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous. Prevent washings from entering water courses, keep fire exposed containers cool by spraying with water.

**Specific hazards arising from the chemical:** In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal decomposition products:** Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN.

**Special protective actions for fire-fighters:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

**Remark:** Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Containers may burst if overheated.

## Section 6 – Accidental Release Measures

---

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate personal protective equipment (see Section 8).

**For emergency responders:** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in “For non-emergency personnel”.

**Environmental precautions:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drain and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods and materials for containment and cleaning up**

If the product is in its solid form: Spilled MDI flakes should be picked up carefully. The area should be vacuum cleaned to remove remaining dust particles completely. If the product is in its liquid form: Absorb spillages onto sand, earth or any suitable adsorbent material. Leave to react for at least 30 minutes. Shovel into open-top drums for further decontamination. Wash the spillage area with water. Test atmosphere for MDI vapour. Neutralize small spillages with decontaminant. Remove and dispose of residues. The compositions of liquid decontaminants are given in Section 16. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

---

## Section 7 – Storage and Handling

---

### Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

**Advice on general occupational hygiene** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** Store in accordance with local regulations. Keep container tightly closed in a cool, well-ventilated place. Keep away from moisture. Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Do not reseal contaminated containers. Uncontaminated containers, free of moisture, may be resealed only after placing under a nitrogen blanket. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.

---

## Section 8 – Exposure Controls/Personal Protection

---

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Diphenylmethane 4,4'-diisocyanate	<b>ACGIH TLV (United States, 3/2012).</b> TWA: 0.005 ppm 8 hours. <b>OSHA PEL (United States, 6/2010).</b> CEIL: 0.02 ppm CEIL: 0.2 mg/m <sup>3</sup>

<b>Appropriate Engineering controls</b>	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Diisocyanates can only be smelled if the occupational exposure limit has been exceeded considerably. Medical supervision of all employees who handle or come in contact with respiratory sensitizers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitization conditions should not work with MDI based products. The Occupational Exposure Limits listed do not apply to previously sensitized individuals. Sensitized individuals should be removed from any further exposure.
<b>Environmental exposure controls</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

<b>Hygiene measures</b>	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Eye/face protection</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
<b>Hand protection</b>	Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include :Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

Contaminated gloves should be decontaminated and disposed of.  
Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier. Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

<b>Body protection</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek-Pro 'F' disposable coverall.
<b>Other skin protection</b>	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Thermal hazards** Not available.

### Section 9 – Physical Properties

---

<b>Physical state:</b>	Liquid
<b>Color:</b>	Not available
<b>Odor:</b>	Not available
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not available
<b>Melting Point/Freezing Point</b>	Not available
<b>Boiling/condensation point:</b>	>300°C decomposes
<b>Flash point:</b>	Closed cup: >110°C (>230°F)[Setaflash]
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Lower and upper explosive (flammable) limits:</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density:</b>	Not available
<b>Relative density:</b>	Not available
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-ctanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	>600°C
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

### Section 10 – Stability and Reactivity

---

<b>Reactivity</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	Stable at room temperature.
<b>Possibility of hazardous</b>	Reaction with water (moisture) produces CO <sub>2</sub> -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.
<b>Conditions to avoid</b>	Avoid high temperatures.
<b>Incompatible materials</b>	Water, alcohols, amines, bases, and acids.
<b>Hazardous Decomposition products</b>	Combustion products may include: carbon oxides (CO, CO <sub>2</sub> ) nitrogen oxides (NO, NO <sub>2</sub> etc.) hydrocarbons and HCN

## Section 11 – Toxicological Information

### Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat – Male, Female	0.49 mg/l
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit – Male, Female	>9400 mg/kg
	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat – Male	>10000 mg/kg
Homopolymer of methylenediphenyl diisocyanate	OECD 403 Acute Inhalation	LC50 Inhalation Dusts And mists	Rat – Male, Female	0.49 mg/l
	OECD 425 Acute Oral Toxicity: Up-and-Down Procedure	LD50 Oral	Rat - Female	>5000 mg/kg
Propylene carbonate	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit – Male, Female	>2000 mg/kg
	No official guidelines	LD50 Oral	Rat – Male, Female	33520 mg/kg

### Conclusion/Summary

Diphenylmethane 4,4'-diisocyanate                      Irritating to respiratory system.

### Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Irritant
	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes – non-irritant.
Homopolymer of methylenediphenyl diisocyanate	OECD 405 Acute Eye Irritation/Corrosion	Rabbit	Eyes – non-irritant.
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin-Irritant
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Non-corrosive
Propylene carbonate	EPA OPPTS	Rabbit	Eyes – Moderate irritant
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin – Non-irritant

### Conclusion/Summary

**Skin :**                      Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate                      No additional information.

Diphenylmethane 4,4'-diisocyanate                      Irritating to skin.

Homopolymer of methylenediphenyl diisocyanate                      Irritating to skin.

Propylene carbonate                      Non-irritating to the skin.

**Eyes :**                      Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate                      No additional information.



Diphenylmethane 4,4'-diisocyanate

Based on the human occupational exposure data, this substance is considered as irritating to eyes.  
Irritating to eyes.

Homopolymer of methylenediphenyl diisocyanate  
Propylene carbonate

Irritating to eyes.

**Respiratory :**

Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate

No additional information.

Diphenylmethane 4,4'-diisocyanate

No additional information

Homopolymer of methylenediphenyl diisocyanate

No additional information

Propylene carbonate

No additional information

**Sensitization**

Product/ingredient name	Test	Route of exposure	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 429 Skin Sensitization: Local Lymph Node Assay	Skin	Mouse	Sensitizing
	OECD 406 Skin Sensitization	Skin	Guinea pig	Not sensitizing
	No official Guidelines	Respiratory	Guinea pig	Sensitizing
Homopolymer of methylenediphenyl diisocyanate	OECD 406 Skin Sensitization	Skin	Guinea pig	Sensitizing
	No official Guidelines	Respiratory	Guinea pig	Sensitizing
Propylene carbonate	No official guidelines	Skin	Human	Not sensitizing
	No official guidelines	Respiratory	Guinea pig	Sensitizing

**Mutagenicity**

Product/ingredient name	Test	Result
Diphenylmethane 4,4'-diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Homopolymer of methylenediphenyl diisocyanate	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
Propylene carbonate	Experiment: In vitro Subject: Mammalian-Animal	Negative
	Experiment: In vitro Subject: bacteria/yeast Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative

**Conclusion/Summary**

Diphenylmethane 4,4'-diisocyanate

No mutagenic effect.

Propylene carbonate

Not mutagenic in a standard battery of genetic

toxicological tests.

**Carcinogenicity**

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
Diphenylmethane 4,4'-diisocyanate	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat – Male, Female	1 mg/m <sup>3</sup>	2 years; 5 days per week	Positive – Inhalation - NOAEL
Homopolymer of Methylenediphenyl Diisocyanate	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat – Male, Female	1 mg/m <sup>3</sup>	2 years; 5 days per week	Negative – Inhalation - NOAEL
Propylene carbonate	OECD 451 Carcinogenicity Studies	Mouse – Male	1500 to 2000 Mg/kg	104 weeks; 2 days per week	Negative – Dermal - NOAEL

**Carcinogenic class**

Product/ingredient name	IARC	OSHA
Diphenylmethane 4,4'-diisocyanate	3	-

**Reproductive toxicity**

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental Effects
Propylene carbonate	OECD 414 Prenatal Developmental Toxicity Study	Rat	Negative	Negative	Negative

**Conclusion/Summary**

Diphenylmethane 4,4'-diisocyanate

No known significant effects or critical hazards

**Teratogenicity**

Product/ingredient name	Test	Species	Result/Result type
Diphenylmethane 4,4'-diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat – Female	Negative - Inhalation
Homopolymer of Methylenediphenyl Diisocyanate	OECD 414 Prenatal Developmental Toxicity Study	Rat – Male, Female	Negative - Inhalation
Propylene carbonate	OECD 414 Prenatal Developmental Toxicity Study	Rat – Male, Female	Negative - Oral

**Conclusion/Summary**

Diphenylmethane 4,4'-diisocyanate

No known significant effects or critical hazards

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	Category 3	Not applicable.	Respiratory tract irritation
Diphenylmethane 4,4'-diisocyanate	Category 3	Not applicable.	Respiratory tract irritation
Homopolymer of methylenediphenyl diisocyanate	Category 3	Not applicable.	Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Not available.

**Information on the likely routes of exposure:**

Not available

**Potential acute Health effects**

- Eye contact:** Causes eye irritation.
- Inhalation:** Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.
- Skin contact:** Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.
- Ingestion:** Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact:** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation:** Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma
- Skin contact:** Adverse symptoms may include the following:  
irritation  
redness
- Ingestion:** No specific data.

**Delayed and immediate effects and also chronic effects from short and long term exposure short term exposure**

**Potential**

**Immediate effects:** Not available.

**Potential delayed effects:** Not available.

**Long term exposure**

**Potential**

**immediate effects:** Not available.

**Potential delayed**

effects: Not available.

### Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
Homopolymer of methylenediphenyl diisocyanate	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	Chronic NOEC Inhalation Dusts and Mists	Rat – Male, Female	0.2 mg/m <sup>3</sup>
	OECD 413 Subchronic Inhalation Toxicity: 90-day study	Sub-chronic NOEC Inhalation Dusts and Mists	Rat – Male, Female	<4 mg/m <sup>3</sup>
Propylene carbonate	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Sub-chronic NOEL Oral	Rat – Male, Female	>5000 mg/kg
	OECD 413 Subchronic Inhalation Toxicity: 90-day Study	Sub-chronic NOEC Inhalation Dusts and mists	Rat – Male, Female	100 mg/m <sup>3</sup>

**General:** May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity:** Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m<sup>3</sup>), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m<sup>3</sup> and no effects at 0.2 mg/m<sup>3</sup>. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

**Mutagenicity:** No known significant effects or critical hazards.

**Teratogenicity:** No known significant effects or critical hazards.

**Developmental** No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother.

**Effects:** Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.

**Fertility** No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute Toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	1.5 mg/1

**Other information:** Not available.

## Section 12 – Ecological Information

### Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Diphenylmethane 4,4'-diisocyanate	OECD 202 Daphnia sp. Acute Immobilisation Test	Acute EC50	24 hours static	Daphnia	>1000 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours static	Fish	>1000 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 days semi-static	Daphnia	>10 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOECr	72 hours static	Algae	1640 mg/l
Homopolymer of methylenediphenyl diisocyanate	OECD 201 Alga, Growth Inhibition Test	Acute EC50	72 hours static	Algae	>1640 mg/l
	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	3 hours static	Bacteria	>100 mg/l
	OECD 202 Daphnia Sp. Acute Immobilisation Test	Acute EC50	24 hours static	Daphnia	>1000 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours static	Fish	>1000 mg/l
	OECD 211 Daphnia Magna Reproduction Test	Chronic NOEC	21 days semi-static	Daphnia	>10 mg/l
Propylene carbonate	DIN DIN 38412 Part 8	Acute EC50	16 Hours	Bacteria	25619 mg/l
	OECD 202 Daphnia sp. Acute Immobilisation Test	Acute EC50	48 hours static	Daphnia	>1000 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute ErC50 (growth rate)	72 hours static	Algae	>900 mg/l
	EU EC C.1 Acute Toxicity for Fish	Acute LC50	96 hours semi-static	Fish	>1000 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOEC	72 hours static	Algae	900 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic NOEC	72 hours static	Algae	929 mg/l

### **Persistence and degradability**

<b>Product/ingredient name</b>	<b>Test</b>	<b>Period</b>	<b>Result</b>
Diphenylmethane 4,4'-diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	28 days	0%
Homopolymer of methylenediphenyl diisocyanate	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	25 days	0%
Propylene carbonate	OECD 301B Ready Biodegradability - CO <sup>2</sup> Evolution Test	29 days	83.5 to 87.7%

### **Conclusion/Summary**

Diphenylmethane 4,4'-diisocyanate                      Not biodegradable

<b>Product/ingredient name</b>	<b>Aquatic half-life</b>	<b>Photolysis</b>	<b>Biodegradability</b>
Diphenylmethane 4,4'-diisocyanate	Fresh Water 0.83 days	-	Not readily
Homopolymer of methylenediphenyl diisocyanate	-	-	Not readily
Propylene carbonate	-	-	Readily

### **Bioaccumulative potential**

<b>Product/ingredient name</b>	<b>LogP<sub>ow</sub></b>	<b>BCF</b>	<b>Potential</b>
Diphenylmethane 4,4'-diisocyanate	4.51	200	Low
Homopolymer of methylenediphenyl diisocyanate	8.56	200	Low
Propylene carbonate	-0.5	-	low

### **Mobility in soil**

**Mobility:** By considering the production and use of the substance, it is unlikely that significant environmental exposure in the air or water will arise. Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino- diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relatively rapid OH radical attack, by calculation and by analogy with related diisocyanates.

### **Other adverse**

**Effects:** Not known significant effects or critical hazards.

### **Other ecological information**

**BOD<sub>5</sub>:** Not determined.

**COD:** Not determined.

**TOC:** Not determined.

---

## **Section 13 – Disposal Consideration**

### **Disposal methods**


The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Section 14 – Transportation Information**

**Proper shipping name**

**DOT:** Other regulated substance, Liquid, NOS (Methylene Diphenyl Diisocyanate)  
**TDG:** Not regulated.  
**IMDG:** Not regulated.  
**IATA:** Not regulated.

Regulatory	UN number	Classes	Packing Group	Label	Additional information
DOT Classification	NA3082	9	III		<b>Reportable quantity 5000 lbs (2270 kg)</b> Single containers less than 5,000 lbs are not regulated.
TDG Classification	Not regulated.	-	-		-
IMDG Classification	Not regulated.	-	-		-
IATA Classification	Not regulated.	-	-		-

**Section 15 – Regulatory Information**

**Safety, health and environmental regulations specific for the product**

**United States Regulations**

**TSCA 8(b) inventory:** All components are listed or exempted.  
**TSCA 5(a)2 final Significant new use Rule (SNUR):** No ingredients listed.  
**TSCA 5(e) substance consent order:** No ingredients listed.  
**TSCA 12(b) export notification:** No ingredients listed.  
**SARA 311/312:** Immediate (acute) health hazard

	Product name	Concentration %
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	Diphenylmethane 4,4'-diisocyanate	23.97-31.262
Clean Air Act – Ozone Depleting Substances (ODS)	This product does not contain nor is it manufactured with ozone depleting substances.	
Sara 313 Form R – Reporting requirements	Diphenylmethane 4,4'-diisocyanate	23.97-31.262

	Ingredient name	%	Section 304 CERCLA Hazardous Substances	CERCLA Reportable Quantity (LBS)	Product Reportable Quantity (LBS)
CERCLA Hazardous Substances	Diphenylmethane 4,4'-dissocyanate	31.2619431442998	Listed	5000	15994
	Propylene oxide	0.00514	Listed	100	1945525

## State regulations

**Pennsylvania – RTK:** Diphenylmethane 4,4'-dissocyanate  
**California Prop 65:** **Warning:** This product contains less than 0.1% of a chemical known to the State Of California to cause cancer.

<u>Ingredient names</u>	<u>Cancer</u>	<u>Reproductive</u>
Propylene oxide	Yes	No

## Canadian regulations

**CEPA DSL:** Diphenylmethane 4,4'-dissocyanate  
**WHMIS Classes:** WHMIS Class D-2A: Material causing other toxic effects (Very toxic).  
WHMIS Class D-2B: Material causing other toxic effects (Toxic).

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.**

## Brazil Regulations

### **Classification system**

**Used:** Norma ABNT-NBR 14725-2:2012

**International lists:**

- Australia inventory (AICS):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory:** Not determined.
- Korea inventory:** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan inventory (CSNN):** Not determined.

---

## **Section 16 – Other Information**

---

### Hazardous Material Information System (USA)

**Health = 2**  
**Flammability = 1**  
**Physical hazards = 1**  
**Personal protection = H**

**The customer is responsible for determining the PPE code for this material.**

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### National Fire Protection Association (USA)

**Health = 2**  
**Flammability = 1**  
**Instability = 1**  
**Special = 0**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : \*- sodium carbonate : 5 - 10 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 2 : \*- concentrated ammonia solution : 3 - 8 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Literature reference: PU 193-1 : 'MDI-Based Compositions : Hazards and Safe Handling Procedures.'

PU 181-15 : Recommended melting procedures for MDI-based isocyanates.

ISOPA Guidelines for safe Loading/Unloading, Transportation, Storage of TDI and MDI , Ref.03-96 PSC-0005-GUIDL.

SPI PMDI User Guidelines for the Chemical Protective Clothing Selection.

References of methods used in the Physico-Chemical Properties section are reported in Annex V part A to

Commission Directive 92/69/EEC of 31 July 1992 adapting to technical progress for the Seventeenth time Council

Directive 67/548/EEC.

#### **Notice to reader**

***While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.***

***IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.***

***THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.***

***Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.***

---

## Safety Data Sheet

---

### OR90WPM, Part B

---

#### Section 1 – Identification

---

Oak Ridge Foam & Coating Systems, Inc  
575 Commercial Ave  
Green Lake, WI 54941  
920-294-6800

Emergency Telephone: (800) 424-9300 Chemtrec  
800-625-9577 (Oak Ridge Foam & Coating Systems, Inc)  
BOTH NUMBERS ARE AVAILABLE DAYS, NIGHTS, WEEKENDS, & HOLIDAYS

**GHS product identifier:** OR90WPM, Part B  
**Other means of identification:** Not available.  
**Product type:** Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

**Product use:** Component of a Polyurethane System

**Supplier's details:** Oak Ridge Foam & Coating Systems, Inc  
575 Commercial Avenue  
Green Lake, WI 54941

**Email address of person responsible for this SDS:** info@oakridgepoly.com

**Emergency telephone number (24h/7 day):** Chemtrec: (800) 424-9300 or (703) 527-3887

---

#### Section 2 – Hazards Identification

---

**OSHA/HCS status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture:**

Acute Toxicity:	4 (oral)
Acute Toxicity:	4 (dermal)
Skin corrosion/irritation	2
Serious eye damage/eye irritation	2
Hazardous to the environment-acute	3
Hazardous to the environment -chronic	3

**GHS Label Elements**

**Hazard pictograms:**



**Signal word:** Danger

**Hazard Statements:** Harmful if inhaled  
 Causes skin and eye irritation.  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 May cause an allergic skin reaction.  
 May cause respiratory irritation.

**Precautionary Statements:** Wear protective gloves. Wear eye or face protection. In case of inadequate ventilation, wear respiratory protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification:** Not available.

### Section 3 – Hazards Identification

Hazardous Components			
Weight Percent	Components	CAS-No.	Classification
50-70%	Poly(oxy(methyl-1,2-ethanediyl)), Alpha-(2-aminomethylethyl) omega-(2-aminomethyletoxy	9046-10-0	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3
15-25%	Aluminum	7429-90-5	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3

5-25%	Diethyltolvenediamine	68479-98-1	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3
5-20%	Glycerol poly (oxypropylene) triamine	64852-22-8	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3
2-10%	4,4'-methylenebis [N-sec-butylaniline]	5285-60-9	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3
.5-1.5%	Stoddard Solvent	8052-41-3	Acute Toxicity- 4 (oral) Acute Toxicity- 4 (dermal) Skin corrosion/irritation-2 Serious eye damage/eye irritation-2 Hazardous to the aquatic environment (acute)-3 Hazardous to the aquatic environment (chronic)-3

The specific chemical identity and/ or exact percentage of components (s) have been withheld as a trade secret.

## Section 4 – First Aid Measures

---

### Description of first aid measures

- Eye contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get Medical attention immediately.
- Inhalation:** Move exposed person to fresh air. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel.
- Skin contact:** After contact with skin, wash immediately with plenty of warm soapy water: Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-TamTm, PEG-400) or corn oil may be more effective than soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

### **Most important symptoms/effects, acute and delayed**

#### **Potential acute health effects**

**Eye contact:** Causes eye irritation

**Inhalation:** Harmful if inhaled. May cause respiratory irritation. This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapor or aerosol at levels above the occupational exposure limit could cause respiratory sensitization. Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitized persons. LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.

**Skin contact:** Causes skin irritation. May cause sensitization by skin contact. Animal studies have shown that respiratory sensitization can be induced by skin contact with known respiratory sensitizers including diisocyanates. These results emphasize the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

**Ingestion:** Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract.

#### **Over-exposure signs/symptoms**

**Eye contact:** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation:** Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma

**Skin contact:** Adverse symptoms may include the following:  
irritation  
redness

**Ingestion:** No specific data

### **Indication of immediate medical attention and special treatment needed, if necessary**

#### **Notes to Physician**

Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: this compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn.

Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound. Inhalation: Treatment is essentially symptomatic. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanata.

## Section 5 – Fire Fighting Measures

---

### Extinguishing media

**Suitable extinguishing media:**

Water spray, dry powder, alcohol-resistant foam, carbon dioxide

**Specific hazards arising from the chemical:**

**Toxic gases/vapors**  
**Depolymerisation and liberation of the mentioned substances/group of substances.**

**Special protective actions for fire-fighters:**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

## Section 6 – Accidental Release Measures

---

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel**

Provide adequate ventilation. Wear appropriate personal protective equipment

**For emergency responders**

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in “For non-emergency personnel”.

**Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drain and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods and materials for containment and cleaning up**

Spills should be contained, solidified, and placed in suitable containers for disposal.

## Section 7 – Storage and Handling

---

### Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing and protective equipment before entering eating areas. Hands and/or face should be washed before breaks and at the end of the shift. When using do not eat, drink or smoke. Keep away from sources of ignition-No smoking. Keep container tightly sealed.

Protection against fire and explosion:

Prevent electrostatic charge- source of ignition should be kept well clear- fire extinguishers should be kept handy.

### **Conditions for safe storage, including any incompatibilities**

Segregate from acids and acid forming substances

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place.

---

## **Section 8 – Exposure Controls/Personal Protection**

---

**Advice on system design:** Provide local exhaust ventilation to control vapors/mist.

### **Personal protective equipment**

#### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) organic vapor/particulate respirator. Do not exceed the maximum use concentration for the respirator facepiece /cartridge combination.

#### **Hand protection:**

Chemical resistant protective gloves

#### **Eye protection:**

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

#### **General safety and hygiene measures:**

Eye wash fountains and safety showers must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Store work clothing separately.

---

## **Section 9 – Physical Properties**

---

<b>Physical state:</b>	Liquid
<b>Color:</b>	Light yellow
<b>Odor:</b>	Negligible
<b>pH:</b>	Not available
<b>Melting Point/Freezing Point</b>	Not available
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Lower and upper explosive (flammable) limits:</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density:</b>	1.06 @ 77°F
<b>Relative density:</b>	1 g/cm <sup>3</sup>
<b>Freezing Point:</b>	Approximately 60°F
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-ctanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available
<b>Flash Point:</b>	Approximately 360°F

## Section 10 – Stability and Reactivity

---

**Reactivity** Under normal conditions of storage and use, hazardous reactions will not occur.

**Stability** Stable under normal conditions of use and storage.

**Conditions to avoid** Void excessive heats. Protect from atmospheric moisture. Replace outage with inert dry nitrogen.

**Incompatible materials** Oxidizing material

**Hazardous Decomposition products** Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Ammonis

## Section 11 – Toxicological Information

---

### Acute toxicity

Product/ingredient name	Endpoint	Species	Result
Poly(oxy(methyl-1,2-thanediy)), Alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)	LD50 Dermal	Rat	2,885 mg/kg
	LD50 Oral	Rabbit	2,980 mg/kg
White Spirit	LD50 Oral	Rat	2,000 mg/kg
Diethyltovenediamine	LD50 Oral	Rat	738 mg/kg
	LD50 Dermal	Rat	2,000 mg/kg
Glycerol poly (oxypropylene) triamine	LD50 Oral	Rat	2,690 mg/kg
	LD50 Dermal	Rabbit	12,500 mg/kg
4,4'-methylenebis[N-sec-butylaniline]	LD50 Oral	Rat	1,380 mg/kg
	LD50 Dermal	Rabbit	3,090 mg/kg
Stoddard Solvent	LD50	No data available	No data available

### Conclusion/Summary

#### Skin

Based on available data, the classification criteria are not met.

#### Eyes

Causes serious eye irritation

#### Respiratory

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (repeated exposure)

Cause damage to organs through prolonged or repeated exposure

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Symptoms/injuries after inhalation

May cause respiratory tract irritation



**Symptoms/injuries after skin contact**

Harmful, in contact with skin. May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Symptoms/injuries after eye contact**

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and teat production, with marked redness and swelling of the conjunctive.

**Symptoms/injuries after ingestion**

Harmful is swallowed. May cause stomach distress, nausea or vomiting

---

**Section 12 – Ecological Information**

---

**Toxicity**

Ecology- general: May cause long-term adverse effects in the aquatic environment.

**Persistence and degradability**

Persistence and degradability: No additional information available.

**Bioaccumulative potential:**

Bioaccumulative potential: No additional information available

**Mobility is soil**

Ecology - soil

**Other adverse effect:**

Effect on ozone layer: No additional information available.

Effect on global warming: No known ecological damage caused by this product.

---

**Section 13 – Disposal Consideration**

---

**Waste treatment methods**

Waste disposal recommendations: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

---

**Section 14 – Transportation Information**

---

**Proper shipping name**

**DOT:** Not regulated.  
**TDG:** Not regulated.  
**IMDG:** Not regulated.  
**IATA:** Not regulated.

---

**Section 15 – Regulatory Information**

---

**U.S Federal Regulations**

**OSHA Hazcom Standard Rating** Hazardous

**US Toxic Substance Control Act** All material ate listed on the TSCA inventory

**SARA Section 3311/312 Hazard Categories:**

Acute health hazard, chronic health hazard, reactivity hazard.

Components: None

**US EPA Emergency Planning and Right-to-Know Act (EPCRA) ASARA Title 111 Section 313 Toxic Chemical (40 CFR 372.65) -Supplier Notification Required:**

Components: None

**US EPA Resource Conservation and Recovery Act (RCRA) Composite list of Hazardous Waste and Appendix V111 Hazardous Constituents (40 CFR 216):**

If discarded in its purchased form, this product would not be hazardous waste wither by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazard waste. (40CFR 261.20-24)

**State Right-to-Know Information**

The following chemicals are specifically listed by individual states' other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements/ For details on your regulatory requirements you should contact the appropriate agency in your state.

This product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.

**California Prop. 65:**

The following detectable components of this product are substances, or belong to class of substance, know to the State of California to cause cancer and/or reproductive toxicity.

---

**Section 16 – Other Information**

---

**NFPA 704M Rating**

**Health = 2**

**Fire = 1**

**Reactivity = 0**

**Other=**

**0=Insignificant 1= Slight 2= Moderate 3= High 4= Extreme**

**HMIS Rating**

**Health = 2\***

**Flammability = 1**

**Physical Hazard= 1**

**0= Minimal 1=Slight 2= Moderate 3= Serious 4= Severe**

**\*= Chronic Health Hazard**

Disclaimer: This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of Oak Ridge Foam & Coating Systems, Inc. Oak Ridge Foam & Coating Systems, Inc. assumes no legal responsibility for use of or reliance upon the information in this MSDS. 11-2016

